


# Industrial Ethernet cables

## CATLine SPE Rugged

Single Pair Ethernet cable for robust indoor and outdoor use



marking example:

SAB BRÖCKSKES · D-VIERSEN · CATLine SPE Rugged 2xAWG26/7 1719-1620 CE

### Construction:

Conductor:	bare copper strands, 7 wires
Insulation:	TPFP
Colour code:	white/blue
Stranding:	twisted to pairs
Inner sheath:	SABIX®
Screen:	alu foil and tinned copper braiding
Wrapping:	non-woven tape
Sheath material:	PUR 420 with mat surface
Sheath colour:	black (RAL 9005)

### Outstanding features:

- » flexible up to -40 °C
- » absolutely weather resistant
- » very easy installation
- » small bending radius

### Technical data:

Peak operating voltage:	max. 90 V
Testing voltage:	core/core 750 V core/screen 750 V
Min. bending radius	
fixed laying:	5 x d
flexible application:	12 x d
Temperature range	
fixed laying:	-50/+90 °C / +125 °C/2500 h
flexible application:	-40/+90 °C / +125 °C/2500 h
Temperature range conductor:	up to +180 °C
Oil resistance:	very good - TMPU acc. to EN 50363-10-2
Chemical resistance:	very good against acids, halogens, bases, chlorinated solvents as well as organic and inorganic compounds
Fuel resistance:	good
Battery acid resistance:	good
UV resistance:	acc. to HD 605
Ozone resistance:	acc. to EN 50396
Salt water resistance:	acc. to UL 1309
Characteristic impedance:	100Ω ± 10Ω, fulfils the electrical and transmission requirements with high frequency with reference to IEC 61156-12. Bandwidth 1 - 600 MHz.
Absence of harmful substances:	acc. to RoHS directive of the European Union, see chapter N „Technical data“

item no.	type	dimension	outer-ø ± 10% mm	copper figure kg/km	cable weight ≈ kg/km
17191620	CATLine SPE Rugged	2 x 26/7 AWG	4,5	16,9	29
17191220	CATLine SPE Rugged	2 x 22/7 AWG	5,7	22,7	39

Other dimensions and colours are possible on request.