

Tray Cables

TR 600 yellow Type TC, MTW and WTTC

UV and oil resistant, flexible Tray Cable and Machine-Tool Cable with yellow cores

WTTC
approval

NFPA 79
for industrial machinery

179 600V c(UL) Type CIC 90°C dry 600V FT1 FT2 FT4 CE



Marking example:

SAB BRÖCKSKES · D-VIERSEN · TR 600 yellow 16 AWG/12c 02901612 TFFN (UL) Type TC-ER 90°C 600V, Oil Resistant I, Sunlight Resistant,

Direct Burial, FT4 (UL) WTTC 90°C 1000V (UL) MTW 16 AWG/37c 600V flexing AWM Style 21179 600V c(UL) Type CIC 90°C dry 600V FT1 FT2 FT4 CE

Construction:

Conductor: bare copper strands with reference to IEC 60228, VDE 0295 class 5 + UL standard 758 table 5.1 + UL 1581 table 20.1

Insulation: special formulated PVC/Nylon

Colour code: yellow cores with numbers, white-yellow ground wire and green-yellow earth wire from 3 cores

Stranding: in layers

Sheath material: special sunlight and oil resistant PVC

Sheath colour: black (RAL 9005)

Outstanding features:

- » Flexible cable for cable tray use
- » Oil resistance
- » Sunlight resistance
- » NFPA 79 for industrial machinery
- » WTTC approval
- » WTTC: UL Subject 2277
- » TC: UL Standard 1277
- » UL recognized, (UL)/c(UL) listed

Technical data:

Voltage
UL-AWM / (UL) / c(UL): 600 V
(UL) WTTC / CSA-AWM: 1000 V

Testing voltage: AWG 18-10 = 6000 V
AWG 8-2 = 7500 V

Min. bending radius:
fixed laying: < 12 mm = 3 x d
> 12 mm = 4 x d

flexible application: < 12 mm = 5 x d
> 12 mm = 6 x d

Radiation resistance: 8 x 10⁷ cJ/kg

Temperature: UL-AWM: up to +105 °C (UL) / c(UL): up to +90 °C
fixed laying: -25 °C

Burning characteristics: (UL) FT4 + c(UL) FT1, FT2, FT4 + CSA FT1, FT2

Oil resistance I: yes

Sunlight resistance: yes

Exposed Runs: yes

Direct Burial: yes

Machinery Area: yes

Absence of harmful substances: acc. to RoHS directive of the European Union, see chapter N „Technical data“

item no.	no. of cores x cross section n x AWG	largest single wire ø mm	outer-ø ± 10% mm	copper figure kg/km	cable weight ≈ kg/km
02901803	3 x 18	0,21	7,7	28,8	83
02901804	4 x 18	0,21	8,3	38,4	99
02901805	5 x 18	0,21	9,0	48,0	118
02901807	7 x 18	0,21	9,8	67,2	146
02901809	9 x 18	0,21	11,9	86,4	194
02901812	12 x 18	0,21	12,5	115,2	227
02901816	16 x 18	0,21	14,6	153,6	310
02901818	18 x 18	0,21	15,3	172,8	343
02901819	19 x 18	0,21	15,3	182,4	352
02901825	25 x 18	0,21	18,1	240,0	450
02901827	27 x 18	0,21	18,1	259,2	476
02901837	37 x 18	0,21	20,1	355,2	620
02901850	50 x 18	0,21	24,6	480,0	868
02901603	3 x 16	0,26	8,3	43,2	103
02901604	4 x 16	0,26	9,0	57,6	123
02901605	5 x 16	0,26	9,8	72,0	148
02901607	7 x 16	0,26	10,7	100,8	186
02901608	8 x 16	0,26	12,3	115,2	222
02901609	9 x 16	0,26	13,1	129,6	248
02901612	12 x 16	0,26	14,5	172,8	313
02901616	16 x 16	0,26	16,0	230,4	397
02901618	18 x 16	0,26	16,8	259,2	439
02901619	19 x 16	0,26	16,8	273,6	453
02901625	25 x 16	0,26	19,9	360,0	581
02901627	27 x 16	0,26	19,9	388,8	616
02901637	37 x 16	0,26	23,3	532,8	862
02901641	41 x 16	0,26	25,0	590,4	957

item no.	no. of cores x cross section n x AWG	largest single wire ø mm	outer-ø ± 10% mm	copper figure kg/km	cable weight ≈ kg/km
02901650	50 x 16	0,26	27,1	720,0	1126
02901661	61 x 16	0,26	28,8	878,4	1336
02901403	3 x 14	0,26	9,2	72,0	138
02901404	4 x 14	0,26	10,0	96,0	168
02901405	5 x 14	0,26	10,9	120,0	202
02901407	7 x 14	0,26	11,9	168,0	258
02901409	9 x 14	0,26	15,4	216,0	362
02901412	12 x 14	0,26	16,1	288,0	434
02901418	18 x 14	0,26	18,8	432,0	613
02901425	25 x 14	0,26	23,5	600,0	878
02901203	3 x 12	0,31	10,5	115,2	194
02901204	4 x 12	0,31	11,4	153,6	238
02901205	5 x 12	0,31	12,5	192,0	289
02901207	7 x 12	0,31	14,4	268,8	394
02901003	3 x 10	0,31	12,4	172,8	279
02901004	4 x 10	0,31	14,2	230,4	366
02901005	5 x 10	0,31	15,6	288,0	443
02901007	7 x 10	0,31	17,0	403,2	573
02900804	4 x 8	0,41	18,1	337,9	579
02900805	5 x 8	0,41	19,9	422,4	716
02900604	4 x 6	0,41	22,8	541,4	908
02900605	5 x 6	0,41	25,1	676,8	1099
02900404	4 x 4	0,41	27,4	844,8	1361
02900405	5 x 4	0,41	30,3	1056,0	1656
02900204	4 x 2	0,41	31,5	1305,6	1928
02900205	5 x 2	0,41	34,9	1632,0	2344

Other dimensions and colours are possible on request.